

KM SEALER F FIRE RESISTANT FILLER



GENERALITY

"KM SEALER F" is a monocomponent fire-proofing putty.

APPLICATION

To seal small holes, cracks or gap to make passive barriers with fire resistance EI 180 - EI 120
The putty has excellent elasticity, weatherproof and waterproof; excellent adhesiveness on many materials, such as: concrete plaster, gypsum, masonry, metal and plastic.

TECHNICAL DATA

| | |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Specific weight: | 1300 g/l |
| Viscosity: | pasty |
| Solids content in weight: | 77% |
| Solids content in volume: | 68% |
| Odour: | completely odourless after drying |
| Drying: | depending on the temperature and humidity; at 25°C 65µr, with room temperature, for 2-3 mm thick of wet product; 24 hours on the surface, 72 hours internally |
| Flashpoint: | non-flammable |
| Dangerous reactions: | none observed |
| Supplied in: | 310 ml cartridges |
| Storage: | 1 years in original closed cartridge not weathered |
| Transport: | no restrictions on land no restrictions ICAO/IATA-DGR (not in direct contact with edible products) |

APPLICATION

Easy to use, with wet stopping knife or extruder; the product is ready to use and requires no preparation, the product should not be diluted.

APPLICATION AMOUNT.

The amount depends on the size of the crack to be sealed.

FURTHER INFORMATION

it does not require any precautionary measures for its use and handling.

Cleaning of tools: with water, immediately after use.

Acute effects to exposure: none.

Safety advice: S7 Keep the container tightly closed; S35 dispose of the product and its cartridge in a safe basket.

Classification and labeling: the mixture does not require any special labeling.

Warnings: none.